Code of Federal Regulations

TITLE 50--Wildlife and Fisheries

CHAPTER VI--FISHERY CONSERVATION AND MANAGEMENT, NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION, DEPARTMENT OF COMMERCE

Part 665, Fisheries in the Western Pacific – §665.812 (a)(5), (a)(6), and (a)(7) Sea Turtle Take Mitigation Measures

§ 665.812 Sea turtle take mitigation measures.
(a) Possession and use of required mitigation gear. The gear required in paragraph (a) of this section must be used according to the sea turtle handling requirements set forth in paragraph (b) of this section.

(1) Hawaii longline limited access permits. Any owner or operator of a vessel registered for use under a Hawaii longline limited access permit must carry aboard the vessel line clippers meeting the minimum design standards specified in paragraph (a)(5) of this section, dip nets meeting the minimum design standards specified in paragraph (a)(6) of this section, and dehookers meeting the minimum design and performance standards specified in paragraph (a)(7) of this section.

(2) Other longline vessels with freeboards of more than 3 ft (0.91m). Any owner or operator of a longline vessel with a permit issued under §665.801 other than a Hawaii limited access longline permit and that has a freeboard of more than 3 ft (0.91 m) must carry aboard the vessel line clippers meeting the minimum design standards specified in paragraph (a)(5) of this section, dip nets meeting the minimum design standards specified in paragraph (a)(6) of this section, and dehookers meeting this minimum design and performance standards specified in paragraph (a)(7) of this section.

(3) Other longline vessels with freeboards of 3 ft (0.91 m) or less. Any owner or operator of a longline vessel with a permit issued under §665.801 other than a Hawaii limited access longline permit and that has a freeboard of 3 ft (0.91 m) or less must carry aboard their vessels line clippers capable of cutting the vessels fishing line or leader within approximately 1 ft (0.3 m) of the eye of an embedded hook, as well as wire or bolt cutters capable of cutting through the vessel's hooks.

(4) Handline, troll, pole-and-line, and other vessels using hooks other than longline vessels. Any owner or operator of a vessel fishing under the Pelagics FEP with hooks other than longline gear are not required to carry specific mitigation gear, but must comply with the handling requirements set forth in paragraph (b) of this section.

Line clippers.

(5) Line clippers are intended to cut fishing line as close as possible to hooked or entangled sea turtles. NMFS has established minimum design standards for line clippers. The Arceneaux line clipper (ALC) is a model line clipper that meets these minimum design standards and may be

fabricated from readily available and low-cost materials (see Figure 3 to this part). The minimum design standards are as follows:

(i) A protected cutting blade. The cutting blade must be curved, recessed, contained in a holder, or otherwise afforded some protection to minimize direct contact of the cutting surface with sea turtles or users of the cutting blade.

(ii) Cutting blade edge. The blade must be capable of cutting 2.0-2.1 mm monofilament line and nylon or polypropylene multistrand material commonly known as braided mainline or tarred mainline.

(iii) An extended reach holder for the cutting blade. The line clipper must have an extended reach handle or pole of at least 6 ft (1.82 m).

(iv) Secure fastener. The cutting blade must be securely fastened to the extended reach handle or pole to ensure effective deployment and use.

Dip nets.

(6) Dip nets are intended to facilitate safe handling of sea turtles and access to sea turtles for purposes of cutting lines in a manner that minimizes injury and trauma to sea turtles. The minimum design standards for dip nets that meet the requirements of this section nets are:

(i) An extended reach handle. The dip net must have an extended reach handle of at least 6 ft (1.82 m) of wood or other rigid material able to support a minimum of 100 lb (34.1 kg) without breaking or significant bending or distortion.

(ii) Size of dip net. The dip net must have a net hoop of at least 31 inches (78.74 cm) inside diameter and a bag depth of at least 38 inches (96.52 cm). The bag mesh openings may be no more than 3 inches by 3 inches (7.62 cm by 7.62 cm).

Dehookers.

(7) (i) Long-handled dehooker for ingested hooks. This item is intended to be used to remove ingested hooks from sea turtles that cannot be boated, and to engage a loose hook when a turtle is entangled but not hooked and line is being removed. One long-handled dehooker for ingested hooks is required on board. The minimum design and performance standards are as follows:

(A) *Hook removal device.* The hook removal device must be constructed of5/16inch (7.94 mm) 316L stainless steel and have a dehooking end no larger than 17/8inches (4.76 cm) outside diameter. The device must be capable of securely engaging and controlling the leader while shielding the barb of the hook to prevent the hook from re-engaging during removal. It must not have any unprotected terminal points (including blunt ones), as these could cause injury to the esophagus during hook removal. The device must be of a size capable of securing the range of hook sizes and styles used by the vessel.

(B) *Extended reach handle.* The hook removal device must be securely fastened to an extended reach handle or pole with a length equal to or greater than 150 percent of the vessel's freeboard or 6 ft (1.83 m), whichever is greater. It is recommended that the handle be designed so that it breaks down into sections. The handle must be sturdy and strong enough to facilitate the secure attachment of the hook removal device.

(ii) Long-handled dehooker for external hooks. This item is intended to be used to remove externally-hooked hooks from sea turtles that cannot be boated. The long-handled dehooker for ingested hooks described in paragraph (a)(7)(i) of this section meets this requirement. The minimum design and performance standards are as follows:

(A) *Construction.* The device must be constructed of5/16inch (7.94 mm) 316 L stainless steel rod. A 5 inch (12.70 cm) tube T-handle of 1 inch (2.54 cm) outside diameter is recommended, but not required. The dehooking end must be blunt with all edges rounded. The device must be of a size capable of securing the range of hook sizes and styles used by the vessel.

(B) *Handle.* The handle must have a length equal to or greater than the vessel's freeboard or 3 ft (0.91 m), whichever is greater.

(iii) Long-handled device to pull an “inverted V.” This item is intended to be used to pull an “inverted V” in the fishing line when disentangling and dehooking entangled sea turtles. One long-handled device to pull an “inverted V” is required on the vessel. The minimum design and performance standards are as follows:

(A) *Hook end.* It must have a hook-shaped end, like that of a standard boat hook or gaff, which must be constructed of stainless steel or aluminum.

(B) *Handle.* The handle must have a length equal to or greater than 150 percent of the vessel's freeboard or 6 ft (1.83 m), whichever is greater. The handle must be sturdy and strong enough to allow the hook end to be effectively used to engage and pull an “inverted V” in the line.

(C) The long-handled dehookers described in paragraphs (a)(7)(i) and (ii) of this section meet this requirement.

(iv) Short-handled dehooker for ingested hooks. This item is intended to be used to remove ingested hooks, externally hooked hooks, and hooks in the front of the mouth of sea turtles that can be boated. One short-handled dehooker for ingested hooks is required on board. The minimum design and performance standards are as follows:

(A) *Hook removal device.* The hook removal device must be constructed of1/4inch (6.35 mm) 316 L stainless steel, and the design of the dehooking end must be such to allow the hook to be secured and the barb shielded without re-engaging during the hook removal process. The dehooking end must be no larger than 1-5/16 inch (3.33 cm) outside diameter. It must not have any unprotected terminal points (including blunt ones), as this could cause injury to the esophagus during hook removal. The dehooking end must be of a size appropriate to secure the range of hook sizes and styles used by the vessel.

(B) *Sliding plastic bite block.* The dehooker must have a sliding plastic bite block, which is intended to be used to protect the sea turtle's beak and facilitate hook removal if the turtle bites down on the dehooker. The bite block must be constructed of a3/4inch (1.91 cm) inside diameter high impact plastic cylinder (for example, Schedule 80 PVC) that is 10 inches (25.40 cm) long. The dehooker and bite block must be configured to allow for 5 inches (12.70 cm) of slide of the bite block along the shaft of the dehooker.

(C) *Shaft and handle.* The shaft must be 16 to 24 inches (40.64 to 60.69 cm) in length, and must have a T-handle 4 to 6 inches (10.16 to 15.24 cm) in length and3/4to 11/4inches (1.90 to 3.18 cm) in diameter.

(v) Short-handled dehooker for external hooks. This item is intended to be used to remove externally hooked hooks from sea turtles that can be boated. One short-handled dehooker for external hooks is required on board. The short-handled dehooker for ingested hooks required to comply with paragraph (a)(7)(v) of this section meets this requirement. The minimum design and performance standards are as follows:

(A) *Hook removal device.* The hook removal device must be constructed of5/16inch (7.94 cm) 316 L stainless steel, and the design must be such that a hook can be rotated out without pulling it out at an angle. The dehooking end must be blunt, and all edges rounded. The device must be of a size appropriate to secure the range of hook sizes and styles used by the vessel.

(B) *Shaft and handle.* The shaft must be 16 to 24 inches (40.64 to 60.69 cm) in length, and must have a T-handle 4 to 6 inches (10.16 to 15.24 cm) in length and3/4to 11/4inches (1.90 to 3.18 cm) in diameter.